

Product Name: WGP Friction+ Roller Bearing Grease Revision: 16.09.2021 Part No 2086136, 2027868

Safety Data Sheet GB according to Regulation (EC) No. 1907/2006

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### **1.1 Product identifier**

Trade name	:	WGP Friction+ Roller Bearing Grease
Product code	:	2086136, 2027868

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture	Automotive and industrial grease.
Uses advised against	This product must not be used in applications other than those listed in Section 1 without first seeking the advice of the supplier.

#### 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier	<ul> <li>Wirtgen GmbH</li> <li>Reinhard Wirtgen Str. 2</li> <li>53578 Windhagen</li> </ul>
Telephone Telefax Email Contact for Safety Data Sheet	: (+49) 2645 131 0 : : If you have any enquiries about the content of this SDS please email customersupport@wirtgen.de
<b>1.4</b> Emergency telephone num	ber : +44 (0) 151 350 4595 (This telephone number is available 24 hours per day, 7 days per week)

### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Based on available data this substance / mixture does not meet the classification criteria.

#### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms	:	No Hazard Symbol required
Signal word	:	No signal word
Hazard statements	:	PHYSICAL HAZARDS:



Product Name: WGP Friction+ Roller Bearing Grease Revision: 16.09.2021 Part No 2086136, 2027868

> Not classified as a physical hazard according to CLP criteria. HEALTH HAZARDS: Not classified as a health hazard under CLP criteria. ENVIRONMENTAL HAZARDS: Not classified as environmental hazard according to CLP criteria.

Precautionary statements	:	Prevention:	
		<b>D</b>	No precautionary phrases.
		Response:	No precautionary phrases.
		Storage:	
		Disposal:	No precautionary phrases.
		Diopotali	No precautionary phrases.

Safety data sheet available on request.



#### 2.3 Other hazards

This mixture does not contain any REACH registered substances that are assessed to be a PBT or a vPvB.

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.

Used grease may contain harmful impurities.

High-pressure injection under the skin may cause serious damage including local necrosis. Not classified as flammable but will burn.

### **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

Chemical nature: A lubricating grease containing highly-refined mineral oils and<br/>additives.<br/>The highly refined mineral oil contains <3% (w/w) DMSO-<br/>extract, according to IP346.<br/>Classification based on DMSO extract content < 3%<br/>(Regulation (EC) 1272/2008, Annex VI, Part 3, Note L).

#### Hazardous components

Chemical name	CAS-No.	Classification	Concentration
	EC-No.	(REGULATION	(% w/w)
	Registration	(EC) No	



Product Name: WGP Friction+ Roller Bearing Grease Revision: 16.09.2021 Part No 2086136, 2027868

	number	1272/2008)	
		/	
Zinc naphthenate	12001-85-3	Skin Sens.1; H317	0.1 - 0.9
	234-409-2	Eye Irrit.2; H319	
	01-2120783834-41	Aquatic Chronic2;	
		H411	
Triazole derivative	91273-04-0	Skin Corr.1B;	0.01 - 0.09
	401-280-0	H314	
		Skin Sens.1A;	
		H317	
		Aquatic Chronic1;	
		H410	
Alkyl thiadiazole		Skin Irrit.2; H315	0.01 - 0.09
	Not Assigned	Skin Sens.1A;	
	948-020-7	H317	
	01-2120792779-28	Acute Tox.4; H332	
		Aquatic Chronic4;	
		H413	

For explanation of abbreviations see section 16.

# **SECTION 4: First aid measures**

# 4.1 Description of first aid measures

Protection of first-aiders	: When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.
If inhaled	: No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice.
In case of skin contact	: Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention.
	When using high pressure equipment, injection of product under the skin can occur. If high pressure injuries occur, the casualty should be sent immediately to a hospital. Do not wait for symptoms to develop. Obtain medical attention even in the absence of apparent wounds.
In case of eye contact	: Flush eye with copious quantities of water. Remove contact lenses, if present and easy to do. Continue rinsing. If persistent irritation occurs, obtain medical attention.
If swallowed	: In general no treatment is necessary unless large quantities are swallowed, however, get medical advice.

4.2 Most important symptoms and effects, both acute and delayed



Product Name: WGP Friction+ Roller Bearing Grease Revision: 16.09.2021 Part No 2086136, 2027868

Symptoms	: Oil acne/folliculitis signs and symptoms may include formation of black pustules and spots on the skin of exposed areas. Ingestion may result in nausea, vomiting and/or diarrhoea.
	Local necrosis is evidenced by delayed onset of pain and tissue damage a few hours following injection.
4.3 Indication of any imm	ediate medical attention and special treatment needed
Treatment	: Notes to doctor/physician: Treat symptomatically.
	High pressure injection injuries require prompt surgical intervention and possibly steroid therapy, to minimise tissue damage and loss of function. Because entry wounds are small and do not reflect the seriousness of the underlying damage, surgical exploration to determine the extent of involvement may be necessary. Local anaesthetics or hot soaks should be avoided because they can contribute to swelling, vasospasm and ischaemia. Prompt surgical decompression, debridement and evacuation of foreign material should be performed under general anaesthetics, and wide exploration is essential.

# **SECTION 5: Firefighting measures**

# 5.1 Extinguishing media

Suitable extinguishing media Unsuitable extinguishing	<ul> <li>Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.</li> <li>Do not use water in a jet.</li> </ul>
media	
5.2 Special hazards arising from	the substance or mixture
Specific hazards during firefighting	: Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide may be evolved if incomplete combustion occurs. Unidentified organic and inorganic compounds.
5.3 Advice for firefighters	
Special protective equipment for firefighters	: Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).
Specific extinguishing methods	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.



Product Name: WGP Friction+ Roller Bearing Grease Revision: 16.09.2021 Part No 2086136, 2027868

#### **SECTION 6: Accidental release measures**

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	: 6.1.1 For non emergency personnel:
	Avoid contact with skin and eyes.
	6.1.2 For emergency responders:
	Avoid contact with skin and eyes.

#### 6.2 Environmental precautions

Environmental precautions : Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers.

#### 6.3 Methods and materials for containment and cleaning up

Methods for cleaning up	
-------------------------	--

: Prevent from spreading or entering into drains, ditches or rivers by using sand, earth, or other appropriate barriers.

#### 6.4 Reference to other sections

For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet., For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet.

# **SECTION 7: Handling and storage**

General Precautions	<ul> <li>Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols.</li> <li>Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.</li> </ul>
7.1 Precautions for safe handling	1
Advice on safe handling	: Avoid prolonged or repeated contact with skin. Avoid inhaling vapour and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires.
7.2 Conditions for safe storage, including any incompatibilities	
Other data	: Keep container tightly closed and in a cool, well-ventilated

place. Use properly labeled and closable containers.



Product Name: WGP Friction+ Roller Bearing Grease Revision: 16.09.2021 Part No 2086136, 2027868

Store at ambient temperature. Refer to section 15 for any additional specific legislation covering the packaging and storage of this product. The storage of this product may be subject to the Control of Pollution (Oil Storage) (England) Regulations. Further guidance may be obtained from the local environmental agency office. Packaging material : Suitable material: For containers or container linings, use mild steel or high density polyethylene. Unsuitable material: PVC. : Polyethylene containers should not be exposed to high **Container Advice** temperatures because of possible risk of distortion. 7.3 Specific end use(s) Specific use(s) : Not applicable.

# **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

#### **Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Oil mist, mineral		TWA	5 mg/m3	US. ACGIH Threshold Limit Values

#### **Biological occupational exposure limits**

No biological limit allocated. **Monitoring Methods** 

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/

Product Name: WGP Friction+ Roller Bearing Grease Revision: 16.09.2021 Part No 2086136, 2027868

> Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany http://www.dguv.de/inhalt/index.jsp L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil

#### 8.2 Exposure controls

**Engineering measures**The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include: Adequate ventilation to control airborne concentrations.

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

General Information:

Define procedures for safe handling and maintenance of controls. Educate and train workers in the hazards and control measures relevant to normal activities associated with this product. Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation. Drain down system prior to equipment break-in or maintenance. Retain drain downs in sealed storage pending disposal or subsequent recycle. Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping. Due to the product's semi-solid consistency, generation of mists and dusts is unlikely to occur.

#### Personal protective equipment

The provided information is made in consideration of the PPE directive (Council Directive 89/686/EEC) and the CEN European Committee for Standardisation (CEN) standards.

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Eye protection	: If material is handled such that it could be splashed into eyes, protective eyewear is recommended. Approved to EU Standard EN166.
Hand protection	
Remarks	: Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. PVC, neoprene or nitrile rubber gloves Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a keyelement of effective hand care. Gloves must only be worn on clean hands. After using

# WIRTGEN GROUP

CLOSE TO OUR CUSTOMERS

Product Name: WGP Friction+ Roller Bearing Grease Revision: 16.09.2021 Part No 2086136, 2027868

	gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.	
	For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model.	
Skin and body protection	: Skin protection is not ordinarily required beyond standard work clothes. It is good practice to wear chemical resistant gloves.	
Respiratory protection	<ul> <li>No respiratory protection is ordinarily required under normal conditions of use.</li> <li>In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material.</li> <li>If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation.</li> <li>Check with respiratory protective equipment suppliers.</li> <li>Where air-filtering respirators are suitable, select an appropriate combination of mask and filter.</li> <li>Select a filter suitable for combined particulate/organic gases and vapours [Type A/Type P boiling point &gt; 65°C (149°F)] meeting EN14387 and EN143.</li> </ul>	
Thermal hazards	Not applicable	
Hygiene measures	Exposure to this product should be reduced as low as reasonably practicable. Reference should be made to the Health and Safety Executive's publication "COSHH Essentials".	
Environmental exposure controls		
General advice	Take appropriate measures to fulfill the requirements of relevant environmental protection legislation. Avoid contamination of the environment by following advice given in Section 6. If necessary, prevent undissolved material from being discharged to waste water. Waste water should be	

VV

Product Name: WGP Friction+ Roller Bearing Grease Revision: 16.09.2021 Part No 2086136, 2027868

> treated in a municipal or industrial waste water treatment plant before discharge to surface water. Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing vapour.

# **SECTION 9: Physical and chemical properties**

# 9.1 Information on basic physical and chemical properties

Appearance	: Semi-solid at ambient temperature.
Colour	: brown
Odour	: Slight hydrocarbon
Odour Threshold	: Data not available
рН	: Not applicable
Dropping point	: 250 °CMethod: IP 396
Melting / freezing point	Not applicable
Initial boiling point and boiling range	: Data not available
Flash point	: Remarks: Not applicable
Evaporation rate	: Data not available
Flammability (solid, gas)	: Data not available
Upper explosion limit	: Typical 10 %(V)
Lower explosion limit	: Typical 1 %(V)
Vapour pressure	: < 0.5 Pa (20 °C) estimated value(s)
Relative vapour density	: > 1estimated value(s)
Relative density	: 1.000 (15 °C)
Density	: 1,000 g/cm3 (15.0 °C) Method: Unspecified
Solubility(ies)	
Water solubility	: negligible
Solubility in other solvents	: Data not available



Product Name: WGP Friction+ Roller Bearing Grease Revision: 16.09.2021 Part No 2086136, 2027868

Partition coefficient: n- octanol/water	: log Pow: > 6(based on information on similar products)
Auto-ignition temperature	: > 320 °C
Decomposition temperature	: Data not available
Viscosity	
Viscosity, dynamic	: Data not available
Viscosity, kinematic	: Not applicable
Explosive properties	: Not classified
Oxidizing properties	: Data not available

### 9.2 Other information

Conductivity

: This material is not expected to be a static accumulator.

# **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.

# 10.2 Chemical stability

Stable.

No hazardous reaction is expected when handled and stored according to provisions

#### 10.3 Possibility of hazardous reactions

Hazardous reactions : Reacts with strong oxidising agents.

#### **10.4 Conditions to avoid**

Conditions to avoid : Extremes of temperature and direct sunlight.

#### 10.5 Incompatible materials

Materials to avoid : Strong oxidising agents.

#### 10.6 Hazardous decomposition products

Hazardous decomposition : No decomposition if stored and applied as directed. products

# **SECTION 11: Toxicological information**

**11.1 Information on toxicological effects** 



Product Name: WGP Friction+ Roller Bearing Grease Revision: 16.09.2021 **Part No 2086136, 2027868** 

Basis for assessment	: Information given is based on data on the components and the toxicology of similar products.Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).
Information on likely routes of exposure	: Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.

#### Acute toxicity

Product:

Acute oral toxicity	: LD50 rat: > 5,000 mg/kg Remarks: Low toxicity: Based on available data, the classification criteria are not met.
Acute inhalation toxicity	: Remarks: Based on available data, the classification criteria are not met.
Acute dermal toxicity	: LD50 Rabbit: > 5,000 mg/kg Remarks: Low toxicity: Based on available data, the classification criteria are not met.

### Skin corrosion/irritation

#### Product:

Remarks: Slightly irritating to skin., Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis., Based on available data, the classification criteria are not met.

# Serious eye damage/eye irritation

### Product:

Remarks: Slightly irritating to the eye., Based on available data, the classification criteria are not met.

# Respiratory or skin sensitisation

#### Product:

Remarks: For respiratory and skin sensitisation:, Not a sensitiser., Based on available data, the classification criteria are not met.

#### Components:

```
Triazole derivative:
```

Remarks: May cause an allergic skin reaction in sensitive individuals.

# Germ cell mutagenicity



Product Name: WGP Friction+ Roller Bearing Grease Revision: 16.09.2021 Part No 2086136, 2027868

# Product:

: Remarks: Non mutagenic, Based on available data, the classification criteria are not met.

#### Carcinogenicity

#### Product:

Remarks: Not a carcinogen., Based on available data, the classification criteria are not met.

Remarks: Product contains mineral oils of types shown to be non-carcinogenic in animal skinpainting studies., Highly refined mineral oils are not classified as carcinogenic by the International Agency for Research on Cancer (IARC).

Material	GHS/CLP Carcinogenicity Classification
Highly refined mineral oil	No carcinogenicity classification.

#### **Reproductive toxicity**

#### Product:

Remarks: Not a developmental toxicant., Does not impair fertility., Based on available data, the classification criteria are not met.

# STOT - single exposure

# Product:

Remarks: Based on available data, the classification criteria are not met.

#### **STOT - repeated exposure**

#### Product:

Remarks: Based on available data, the classification criteria are not met.

#### Aspiration toxicity

#### Product:

Not an aspiration hazard.

#### Further information

Product:



Product Name: WGP Friction+ Roller Bearing Grease Revision: 16.09.2021 Part No 2086136, 2027868

Remarks: Used grease may contain harmful impurities that have accumulated during use. The concentration of such harmful impurities will depend on use and they may present risks to health and the environment on disposal., ALL used grease should be handled with caution and skin contact avoided as far as possible.

Remarks: High pressure injection of product into the skin may lead to local necrosis if the product is not surgically removed.

Remarks: Slightly irritating to respiratory system.

Remarks: Classifications by other authorities under varying regulatory frameworks may exist.

#### Summary on evaluation of the CMR properties

Germ cell mutagenicity- Assessment	: This product does not meet the criteria for classification in categories 1A/1B.
Carcinogenicity - Assessment	: This product does not meet the criteria for classification in categories 1A/1B.
Reproductive toxicity - Assessment	: This product does not meet the criteria for classification in categories 1A/1B.

#### **SECTION 12: Ecological information**

### 12.1 Toxicity

Basis for assessment	: Ecotoxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the ecotoxicology of similar products. Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).(LL/EL/IL50 expressed as the nominal amount of product required to prepare aqueous test extract).
Toxicity to fish (Acute toxicity)	: Remarks: LL/EL/IL50 > 100 mg/l Practically non toxic: Based on available data, the classification criteria are not met.
Toxicity to crustacean (Acute toxicity)	: Remarks: LL/EL/IL50 > 100 mg/l Practically non toxic: Based on available data, the classification criteria are not met.
Toxicity to algae/aquatic	: Remarks: LL/EL/IL50 > 100 mg/l



# Product Name: WGP Friction+ Roller Bearing Grease Revision: 16.09.2021 Part No 2086136, 2027868

plants (Acute toxicity)	Practically non toxic: Based on available data, the classification criteria are not met.
Toxicity to fish (Chronic toxicity)	: Remarks: Based on available data, the classification criteria are not met.
Toxicity to crustacean (Chronic toxicity)	: Remarks: Based on available data, the classification criteria are not met.
Toxicity to microorganisms (Acute toxicity)	: Remarks: Based on available data, the classification criteria are not met.

# Components: Triazole derivative :

M-Factor (Short-term (acute)	: 1
aquatic hazard)	
M-Factor (Long-term	: 1
(chronic) aquatic hazard)	

# 12.2 Persistence and degradability

#### Product:

Biodegradability	: Remarks: Not readily biodegradable., Major constituents are
	inherently biodegradable, but contains components that may
	persist in the environment.

# 12.3 Bioaccumulative potential

# Product:

Bioaccumulation	: Remarks: Contains components with the potential to bioaccumulate.
Partition coefficient: n- octanol/water	: log Pow: > 6Remarks: (based on information on similar products)
12.4 Mobility in soil	
Product:	
Mobility	: Remarks: Semi-solid under most environmental conditions., If it enters soil, it will adsorb to soil particles and will not be mobile. Remarks: Floats on water.

# 12.5 Results of PBT and vPvB assessment

# Product:

Assessment	: This mixture does not contain any REACH registered
	substances that are assessed to be a PBT or a vPvB.

# 12.6 Other adverse effects



Product Name: WGP Friction+ Roller Bearing Grease Revision: 16.09.2021 Part No 2086136, 2027868

# Product:

Additional ecological information	: Does not have ozone depletion potential, photochemical ozone creation potential or global warming potential., Product is a mixture of non-volatile components, which will not be released to air in any significant quantities under normal
	conditions of use. Poorly soluble mixture., Causes physical fouling of aquatic
	organisms. Mineral oil does not cause chronic toxicity to aquatic organisms at concentrations less than 1 mg/l.
	organisms at concentrations less than 1 mg/l.

# **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Product	<ul> <li>Recover or recycle if possible.</li> <li>It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.</li> <li>Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment. Do not dispose into the environment, in drains or in water courses</li> <li>Do not dispose of tank water bottoms by allowing them to drain into the ground. This will result in soil and groundwater contamination.</li> <li>Waste arising from a spillage or tank cleaning should be disposed of in accordance with prevailing regulations, preferably to a recognised collector or contractor. The competence of the collector or contractor should be established beforehand.</li> </ul>
	MARPOL - see International Convention for the Prevention of Pollution from Ships (MARPOL 73/78) which provides technical aspects at controlling pollutions from ships.
Contaminated packaging	: Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand. Disposal should be in accordance with applicable regional, national, and local laws and regulations.
Local legislation	
Waste catalogue	:
	EU Waste Disposal Code (EWC):

Product Name: WGP Friction+ Roller Bearing Grease Revision: 16.09.2021 Part No 2086136, 2027868

Waste Code	:
	12 01 12*
Remarks	: Disposal should be in accordance with applicable regional, national, and local laws and regulations.
	Classification of waste is always the responsibility of the end user.

# **SECTION 14: Transport information**

14.1 UN number		
ADR	: Not regulated as a dangerous good	
RID	: Not regulated as a dangerous good	
IMDG	: Not regulated as a dangerous good	
ΙΑΤΑ	: Not regulated as a dangerous good	
14.2 Proper shipping name		
ADR	: Not regulated as a dangerous good	
RID	: Not regulated as a dangerous good	
IMDG	: Not regulated as a dangerous good	
ΙΑΤΑ	: Not regulated as a dangerous good	
14.3 Transport hazard class		
ADR	: Not regulated as a dangerous good	
RID	: Not regulated as a dangerous good	
IMDG	: Not regulated as a dangerous good	
ΙΑΤΑ	: Not regulated as a dangerous good	
14.4 Packing group		
ADR	: Not regulated as a dangerous good	
RID	: Not regulated as a dangerous good	
IMDG	: Not regulated as a dangerous good	
ΙΑΤΑ	: Not regulated as a dangerous good	
14.5 Environmental hazards		
ADR	: Not regulated as a dangerous good	
RID	: Not regulated as a dangerous good	
IMDG	: Not regulated as a dangerous good	
14.6 Special precautions for user		
Remarks	: Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.	

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied. MARPOL Annex 1 rules apply for bulk shipments by sea.



Product Name: WGP Friction+ Roller Bearing Grease Revision: 16.09.2021 Part No 2086136, 2027868

#### SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - List of substances subject to authorisation (Annex XIV)	: Product is not subject to Authorisation under REACH.
---	---

Volatile organic compounds : 0 %

Other regulations

: The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

Environmental Protection Act 1990 (as amended). Health and Safety at Work etc. Act 1974. Consumers Protection Act 1987. Pollution Prevention and Control Act 1999. Environment Act 1995. Factories Act 1961. The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment (Amendment) Regulations 2011. Chemicals (Hazard Information and Packaging for Supply) Regulations 2009. Control of Substances Hazardous to Health Regulations 2002 (as amended). Merchant Shipping (Dangerous Goods and Marine Pollutants) Regulations 1997. Reporting of Injuries, Diseases and Dangerous Occurrences Regulations 1995 (as amended). Personal Protective Equipment Regulations 2002. Personal Protective Equipment at Work Regulations 1992. Hazardous Waste (England and Wales) Regulations 2005(as amended). Control of Major Accident Hazards Regulations 1999 (as amended). Renewable Transport Fuel Obligations Order 2007 (as amended). Energy Act 2011. Environmental Permitting (England and Wales) Regulations 2010 (as amended). Waste (England and Wales) Regulations 2011 (as amended). Planning (Hazardous Substances) Act 1990 and associated regulations. The Environmental Protection (Controls on Ozone-Depleting Substances) Regulations 2011.

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), annex XIV. Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), annex XVII. Directive 2004/37/EC on the protection of workers from the risks related to exposure to carcinogens or mutagens at work and its amendments. Directive 1994/33/EC on the protection of young people at work and its amendments.

Council Directive 92/85/EEC on the introduction of measures



Product Name: WGP Friction+ Roller Bearing Grease Revision: 16.09.2021 Part No 2086136, 2027868

> to encourage improvements in the safety and health at work of pregnant workers and workers who have recently given birth or are breastfeeding and its amendments.

# The components of this product are reported in the following inventories:

REACH TSCA

: Notified with Restrictions. : All components listed.

#### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

#### **SECTION 16: Other information**

,

# Full text of H-Statements

H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

#### Full text of other abbreviations

Acute Tox. Aquatic Chronic Eye Irrit. Skin Corr. Skin Irrit. Skin Sens. Abbreviations and Acro	Acute toxicity Long-term (chronic) aquatic hazard Eye irritation Skin corrosion Skin irritation Skin sensitisation nyms : The standard abbreviations and acronyms used in this document can be looked up in reference literature (e.g. scientific dictionaries) and/or websites.
	ACGIH = American Conference of Governmental Industrial Hygienists ADR = European Agreement concerning the International Carriage of Dangerous Goods by Road AICS = Australian Inventory of Chemical Substances ASTM = American Society for Testing and Materials BEL = Biological exposure limits BTEX = Benzene, Toluene, Ethylbenzene, Xylenes CAS = Chemical Abstracts Service CEFIC = European Chemical Industry Council CLP = Classification Packaging and Labelling COC = Cleveland Open-Cup



Product Name: WGP Friction+ Roller Bearing Grease Revision: 16.09.2021 Part No 2086136, 2027868

> DIN = Deutsches Institut fur Normung DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level DSL = Canada Domestic Substance List EC = European Commission EC50 = Effective Concentration fifty ECETOC = European Center on Ecotoxicology and Toxicology Of Chemicals ECHA = European Chemicals Agency EINECS = The European Inventory of Existing Commercial **Chemical Substances** EL50 = Effective Loading fifty ENCS = Japanese Existing and New Chemical Substances Inventory EWC = European Waste Code GHS = Globally Harmonised System of Classification and Labelling of Chemicals IARC = International Agency for Research on Cancer IATA = International Air Transport Association IC50 = Inhibitory Concentration fifty IL50 = Inhibitory Level fifty IMDG = International Maritime Dangerous Goods INV = Chinese Chemicals Inventory IP346 = Institute of Petroleum test method N° 346 for the determination of polycyclic aromatics DMSO-extractables KECI = Korea Existing Chemicals Inventory LC50 = Lethal Concentration fifty LD50 = Lethal Dose fifty per cent. LL/EL/IL = Lethal Loading/Effective Loading/Inhibitory loading LL50 = Lethal Loading fifty MARPOL = International Convention for the Prevention of **Pollution From Ships** NOEC/NOEL = No Observed Effect Concentration / No **Observed Effect Level** OE HPV = Occupational Exposure - High Production Volume PBT = Persistent, Bioaccumulative and Toxic PICCS = Philippine Inventory of Chemicals and Chemical Substances PNEC = Predicted No Effect Concentration REACH = Registration Evaluation And Authorisation Of Chemicals RID = Regulations Relating to International Carriage of Dangerous Goods by Rail SKIN\_DES = Skin Designation STEL = Short term exposure limit TRA = Targeted Risk Assessment TSCA = US Toxic Substances Control Act TWA = Time-Weighted Average vPvB = very Persistent and very Bioaccumulative

#### **Further information**

Other information

: A vertical bar () in the left margin indicates an amendment



Product Name: WGP Friction+ Roller Bearing Grease Revision: 16.09.2021 Part No 2086136, 2027868

from the previous version.

No Exposure Scenario annex is attached to this safety data sheet. It is a non-classified mixture containing hazardous substances as detailed in Section 3; relevant information from Exposure Scenarios for the hazardous substances contained have been integrated into the core sections 1-16 of this SDS.

There has been a significant change in compositional information in section 2 & 3.

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.